

Specifications of 665/O/P/WH

Features: 7" LCD Wireless HDMI Monitor with WHDI Technology.

LCD Display	LCD Size	7 inch			
	Display Resolution(Dot)	1024 × R.G.B. × 600			
	Active area	153.6(H) x 90(V) mm			
	Dot pitch	0.15(H) x 0.15(V) mm			
	Aspect Ratio	17:10			
	Brightness	250 cd/m ²			
	Contrast Ratio	800:1			
	Back-light	White LED			
	Surface treatment	Hard coating with EWV Flim			
	Response Time Note1		Symbol	Min (mm)	Typ. (mm)
		Horizontal	165.45	165.75	166.05
		Vertical	105.09	105.39	105.69
		Depth	-	3.4	3.7
View Angle(Degree)	80/80(Left/Right) and 80/70(Up/Down)				
Interface	AV, YPbPr, HDMI, Mini XLR, DC Power				
Input Connector	WHDI, HDMI, YPbPr, AV				
Output Connector	HDMI, Video				
Power	DC 12V, 1500mA				
Power Consumption	≤12Watts				
Control	Basic	Power, Video, YPbPr, HDMI&WHDI bottoms. F1-F4 User-definable buttons, BRI/MENU knob, SAT/ADJ knob, TINT knob, CONT knob			
	Advance	Brightness, Contrast, Saturation, Tint, Volume, Sharpness, Color Temp, Check Field, Aspect Ratio, Pixel-to-Pixel, Camera, H/V delay, Underscan, Center Marker, Screen Markers, Language, PIP, Input Format OSD, LOGO, Freeze Input, Image Flip, Assistant Func., Manufacturer Default, Color Bar, Zoom, Peaking, False Color, Exposure, Histogram.			
Speaker	Built in, 1 Watts				
Menu Language	English/Chinese				

Storage Temperature	$(-30)^{\circ}\text{C} \sim (+70)^{\circ}\text{C}$	
Operation Temperature	$(-20)^{\circ}\text{C} \sim (+60)^{\circ}\text{C}$	
Operation at High Temperature and High Humidity	$T_a = +60^{\circ}\text{C}$, 240hrs	
Product Dimension(mm)	194.5(L) \times 150(W) \times 38.5(D)	
Package Contents	Monitor, WHDI transmitter, Flexible folding sun shade, Battery plates, Battery plate bracket, DC adapter, HDMI A/C cable, Manual	
Warranty	1 year parts and labor in Depot of City of Industry, CA	

Note Definition of Response Time : Sum of T_R and T_F



