

## 667GL-70NP/H/Y/S

LCD Display	Lcd Size	7.0 inch(Diagonal)		
	Type	a-Si TFT active matrix		
	Native Resolution	800X3(RGB)X480		
		Support display up to 1,920 × 1,080		
	Active area	152.4 (W)X91.44 (H) mm		
	Dot pitch	0.0635(W)X0.1905(H) mm		
	Aspect Ratio	16:9		
	Brightness	450 CD/M <sup>2</sup>		
	Contrast Ratio	500:1		
	Light Source	LED		
	Surface treatment	Anti-Glare		
	Response Time		Typical	Max
	(Note 1)	T on	10 msec	20 msec
		T off	15 msec	30 msec
	View Angle	120°/140° (H/V)		
Video Input Signal	YPrPb			
	RCA Video Input			
	HDMI			
	<b>HD-SDI</b>			
Inputs	1Component input (YPrPb), 2 RCA Video Inputs, 1 RCA Audio Input, 1HDMI, HD-SDI			
Power	AC adapter to DC DC : 12V, 1200 mA	Input: 100-240V, 50/60Hz, 0.60A Output: 12V, 1200 mA		
	External Battery	7.2V battery, 2 Battery adapters included		
Power Consumption	Ö8 Watts			
Control	Basic	Power, Auto Adjustment, Source, Brightness up/down, 4 Levels Brightness by one button, OSD Menu		
	Advance	Adjust Brightness, Contrast, Saturation, Tint, Sharpness, Phase, Clock, Color Temperature, H position, V position, OSD Language		
Speaker	Built in, × 250mW			
Remote Control	Infrared remote Control			
Cabinet Color	Black			
Storage temperature	(-20)°C ó(+ 70°)C			
Operation Temperature	(-10)°C ó(+ 60°)C			
Operation at High Temperature and Humidity	(+ 40°)C, 90% RH Max			
Product Dimension (without Stand)	185.5×133.8×37.5mm			
Package Contents	Monitor, Sun Shade, DV battery mount plate model A & B, 12V 1.5A DC adapter, Remote Control, Stand, Manual			

# 667GL-70NP/H/Y/S

Warranty	One year standard warranty including parts and labor	

Note 1: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time ( $T_{ON}$ ) is the time between photo detector output intensity changed from 90% to 10%. And fall time ( $T_{OFF}$ ) is the time between photo detector output intensity changed from 10% to 90%.

